

# Himalaya G10 Black Series

## 430-450W

108-cell Bifacial Half Cell  
Double-glass Solar Module



### HJT 3.0

Combining gettering process and double-sided  $\mu\text{c-Si}$  to maximize cell efficiency and module power.



### -0.26%/°C $P_{\text{max}}$ temperature coefficient

More stable power generation performance and even better in hot climate.



### Small Chamfer Design

Bigger power generation area on the solar cell, increasing 1% cell power of single piece.



### SMBB design with Half-Cut Technology

Shorter current transmission distance, less resistive loss and higher cell efficiency.



### Up to 90% Bifaciality

Natural symmetrical bifacial structure bringing more energy yield from the backside.



### Sealing with PIB based sealant

Stronger water resistance, greater air impermeability to extend module lifespan.



### Higher reliability

Industrial leading product and performance warranty, ensuring modules' consistent outstanding performance.



### Ideal choice for residential rooftop

## WARRANTY

Product  
Warranty **30**  
years

Linear  
Power  
Warranty **30**  
years



**ANHUI HUASUN ENERGY CO., LTD.**

All rights reserved © 2020-2023  
Made In China



The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Anhui Huasun reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the latest version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.


# Himalaya G10 Black Series 430-450W

108-cell Bifacial HJT Solar Half Cell Module

- BloombergNEF Tier 1 PV module manufacturer
- Reinsurance underwritten by Ariel Re

## Engineering Drawings

Unit: mm



## Electrical Characteristics (STC\*)

HS-182-B108	DSB430	DSB435	DSB440	DSB445	DSB450
Maximum Power (P <sub>max</sub> )	430W	435W	440W	445W	450W
Module Efficiency (%)	22.02%	22.28%	22.53%	22.79%	23.04%
Optimum Operating Voltage (V <sub>mp</sub> )	34.60V	34.86V	35.12V	35.38V	35.63V
Optimum Operating Current (I <sub>mp</sub> )	12.43A	12.48A	12.53A	12.58A	12.63A
Open Circuit Voltage (V <sub>oc</sub> )	41.37V	41.64V	41.91V	42.18V	42.44V
Short Circuit Current (I <sub>sc</sub> )	12.95A	13.00A	13.05A	13.10A	13.15A
Operating Module Temperature	-40 to +85 °C				
Maximum System Voltage	DC1500V (IEC)				
Maximum Series Fuse	25A				
Power Tolerance	0~+5W				
Bifaciality	85% ± 5%				

\*STC: Irradiance 1000 W/m<sup>2</sup>, cell temperature 25 °C, AM=1.5. Tolerance of P<sub>max</sub> is within +/- 3%.

## BSTC\*\*

Maximum Power (P <sub>max</sub> )	475W	480W	485W	490W	495W
Optimum Operating Voltage (V <sub>mp</sub> )	34.60V	34.86V	35.12V	35.38V	35.63V
Optimum Operating Current (I <sub>mp</sub> )	13.73A	13.77A	13.81A	13.85A	13.90A
Open Circuit Voltage (V <sub>oc</sub> )	41.37V	41.64V	41.91V	42.18V	42.44V
Short Circuit Current (I <sub>sc</sub> )	14.31A	14.34A	14.38A	14.42A	14.47A

\*\*BSTC: Front side irradiation 1000W/m<sup>2</sup>, back side reflection irradiation 135W/m<sup>2</sup>, AM=1.5, ambient temperature 25 °C.


## Temperature Characteristics

Nominal Operating Cell Temp. (NOCT)	44 °C ± 2 °C
Temperature Coefficient of P <sub>max</sub>	-0.26%/°C
Temperature Coefficient of V <sub>oc</sub>	-0.24%/°C
Temperature Coefficient of I <sub>sc</sub>	0.04%/°C

## Safety & Warranty

Safety Class	Class II
Fire Safety Class	Class C according to UL790
Product Warranty	30 yrs Workmanship
Performance Warranty	30 yrs Linear Warranty*

\* Less than 1% attenuation in the 1st year, the annual attenuation from the 2nd year is no more than 0.375%, and the power is no less than 88% until the 30th year.



\* Refer to HUASUN standard warranty for details

## Mechanical Characteristics

Cell Type	HJT Mono 182×91.75mm
Cell Connection	108 (6×18)
Module Dimension	1722×1134×30 mm
Weight	22kg
Junction Box	IP68
Output Cable	4mm <sup>2</sup> , 1200mm in length, length can be customized / UV resistant
Connectors Type	PV-KST4-EVO 2/xy_UR / PV-KBT4-EVO 2/xy_UR/ 05-8 / RHC2xyzu / UTXCFabcd / UTXCMabcd / PV4-S1yx / PV-H4
Frame	Anodised aluminum alloy (Black)
Front Load	5400 Pa
Rear Load	2400 Pa
Glass Thickness	Double glass, 2.0mm/1.6mm

## Shipping Configurations

Container Size	HC
Pallets Per Container	40'
Modules Per Pallet (pcs)	26
Modules Per Container (pcs)	36
	936

ANHUI HUASUN ENERGY CO., LTD.

All rights reserved © 2020-2023

Made In China

NO.99 Qingliu Road, Economic and Technological Development Zone, Xuancheng, Anhui, China

Tel: 0086-563-3318095 www.huasunsolar.com

sales@huasunsolar.com customerservice@huasunsolar.com