

F SERIES (G2)

DUAL MPPT INVERTERS



High Performance

Low start-up voltage, wide voltage range, 97.4% maximum efficiency.



Easy Installation

Flexible configuration, plug and play set-up.



IP65 Rated

Engineered to last with maximum flexibility. Suitable for outdoor installation.



Remote Monitoring

Monitor your system remotely via smartphone app or web portal.

ANYTIME, ANYWHERE REMOTE MONITORING PLATFORM

Monitor system performance in real-time via smartphone app or web portal using our advanced monitoring platform.



F SERIES (G2)



For more about the Fox ESS range of single-phase inverters, visit:

WWW.FOX-ESS.COM



TECHNICAL SPECIFICATIONS

Model	F3000-G2	F3600-G2	F4600-G2	F5000-G2	F5300-G2	F6000-G2
INPUT(PV)						
Max. Input Power [W]	4500	5400	6900	7500	7950	9000
Max./Min. Input Voltage [V]	600/80	600/80	600/80	600/80	600/80	600/80
Start-up Input Voltage [V]	120	120	120	120	120	120
Rated Input Voltage [V]	360	360	360	360	360	360
MPPT Operating Voltage Range [V]	80 ~ 550					
Max. Input Current[A]	14					
Max. Short-circuit Current [A]	18					
No. of Independent MPP Trackers	2					
No. of Strings per MPP Tracker	1					
OUTPUT(AC)						
Rated Output Apparent Power [VA]	3000	3600	4600	5000	5300	6000
Max. Output Apparent Power [VA]	3300	3960	5060	5500	5830	6000
Rated Grid Voltage [Vac]	220/ 230/ 240					
Rated Grid Frequency [Hz]	50/ 60					
Rated Output Current [A]	13.0	15.7	20.0	21.7	23.0	26.1
Max. Output Current [A]	14.3	17.2	22.0	23.9	25.3	26.1
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)					
Total Harmonic Distortion (THDi) [%]	<3					
EFFICIENCY						
MPPT Efficiency [%]	99.00					
Euro-efficiency [%]	96.80					
Max. Efficiency [%]	97.40					
PROTECTION						
Insulation Monitoring	YES					
Residual Current Monitoring	YES					
PV String Current Monitoring	YES					
DC Reverse Polarity Protection	YES					
Anti-islanding Protection	YES					
AC Short-circuit Protection	YES					
AC Overcurrent Protection	YES					
AC Overvoltage Protection	YES					
Surge Protection	Optional (DC/AC: Type II)					
DC Switch	Optional					
AFCI	NO					
GENERAL DATA						
Dimensions (W*H*D) [mm]	402*453*148					
Weight [kg]	14.8					
Cooling Method	Natural Convection					
Topology	Transformerless					
Noise Emission (typical) [dB]	<30					
Max. Operating Altitude [m]	3000					
Operating Temperature Range [°C]	-25 ~ 60					
Humidity [%]	0 ~ 100 (No Condensation)					
Ingress Protection	IP65					
Internal Consumption at Night [W]	<1					
Monitoring Module	LAN/ WIFI / GPRS / 4G (Optional)					
Communication	RS485, Meter / CT, DRM					
Display	LCD, Touch Key, App, Website					
Country Of Manufacture	China					
STANDARD COMPLIANCE (MORE AVAILABLE UPON REQUEST)						
Safety	EN/IEC 62109-1/2					
EMC	EN 61000-6-1/2/3/4					
Grid Regulation	AS/NZS-4777.2, CEI 0-21					